

RIDER R 65 FD 65

COMPACT RIDE ON SCRUBBER DRYER RIDER SERIES

Rider R 65 is the new compact ride on scrubber dryer in Ghibli & Wirbel's range. 65 liters of tank capacity together with high productivity (3250 m²/h) and running time, guarantees the perfect solution in any kind of environment. Every details has been studied to guarantee the perfect ergonomics and ease of use. The main distinctive feature is the incredible manoeuvrability; cleaning closed to wall in small areas and making the impossible U-Turn operation (only 115 cm), makes Rider the perfect choice for those who work in the most narrow and congested areas. The machine is suitable also for day cleaning in sensitive areas like hospitals and schools, thanks to the low noise level. The FD 65 version, with front traction, is equipped with the innovative brush head system: four small brushes with an excellent down pressure, surrounding the driving wheel, for the best floor coverage and cleaning results, even in small spaces or congested areas. Rider compact squeegee (750 mm) naturally adapt itself to every movements of the machine. The results are excellent drying performance on every kind of surface even in sharp curves and during the impossible U - turn operation. The BC version is equipped with external battery charger and battery set (105 Ah): it allows more than two hours and a half of working session without any stop!



Lever lifting/regulation system (squeegee, brush deck, water flow)



Immediate opening/access to all the main components




Wide rec. tank opening: easy to clean



Compact and responsive squeegee



Brushes easy to install/remove



Outstanding 4 brushes-deck system



U-Turn operation (only 115 cm)



Compact and reactive: you can go everywhere

PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
RIDER R 65 FD 65	10.0654.00	1
RIDER R 65 FD 65 BC	13.0654.00	1

TECHNICAL DATA

FEATURES

Cleaning width	mm	650
Squeegee width	mm	750
Productivity (theor./practical)	m ² /h	3250 - 1950
Power supply		Battery 24 V
Installed power	W	1650
Advancement		with traction

BRUSHES

Diameter - Pad x No	mm - inch x nr	180 - 7" x 4
Motor rating x No	W x nr	100 x 4
Motor speed	rpm	190
Down pressure - Contact pressure	Kg - g /cm ²	22 - 20,4

TRACTION

Motor rating	W	700
Driving speed	Km/h	5
Hill climbing ability	%	5

VACUUM

Motor rating	W	550
Vacuum	mbar/mmH2O	1791
Airflow rating	l/s	30
Noise level	dB(A)	64

TANK

Type		Double tank
Cleaning solution tank	l	65
Recovery tank	l	65
Weight (empty/with batteries)	Kg	140/220
Dimensions	mm	1150x780x1425

STANDARD ACCESSORIES

TYPE	REF. NO.
Polypropylene brush 7" Ø 0,6 (*)	4905-0037-0
External battery charger 24V 20A (**)	18.0063.00
Battery set (2 uts) 12V 105 Ah (**)	18.0001.00
Set rubber squeegee blades 750 mm (front/rear)	96.0091.00

OPTIONAL ACCESSORIES

TYPE	REF. NO.
Pad driver 7"	4915-0011-0
Tynex brush 7"	4905-0041-0
Set polyurethane squeegee blades 750 mm (front/rear)	96.0092.00

(*) 4 brushes on standard equipment

(**) Only for BC version